

Things you need:

- 1 liter bio ethanol
- Soft scrub pad
- Pressure sprayer

Graffiti removal advice

Anti graffiti coatings

We offer a wide range of coatings that protects your building against graffiti vandalism. The special pigmentation in the coating makes it easy to remove graffiti. Our range of anti-graffiti coatings consists of EuraPrestige, Active FastClean and PVDF LUM coatings.

Graffiti removal in 3 steps

1. Start by cleaning the surface with pressure washing (max. 50 bars) to remove dirt. In general hot water on metal surfaces is the most effective way to break the bond of the graffiti. Use water with a temperature of max. 80°C. In some cases this will be enough to remove the main part of the graffiti. If not, go to the next step.
2. Treat the graffiti with bio ethanol. Use a soft scrub pad and carefully clean the facade. Make sure that you treat the total graffiti area and allow the bio-ethanol a few minutes contact to ensure proper removal.
3. Use the pressure washer to remove the graffiti from the building. If the graffiti is not completely removed, repeat steps 1 to 3 until a satisfactory result is achieved.

The final result is a facade clean of graffiti. Graffiti vandals will stay away from your building, knowing that graffiti can be removed quickly.

We do not take responsibility for any damage that is caused to the facade by following this advising document, as we are not supplier of graffiti removal products. We always recommend to start with a trial run on a small piece of the façade before you treat the total surface



Information

Architectural Support

T +31 (0)475 370 341

E max@euramax.eu

I www.euramax.eu



Euramax